SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PRO-SET INF-210 HARDENER
UFI : W000-A0PG-V007-29GA

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Hardener

1.2.2. Uses advised against

Restrictions on use : No uses have been identified that are advised against

1.3. Details of the supplier of the safety data sheet

Manufacturer
Wessex Resins & Adhesives Limited
Cupernham House Cupernham Lane
SO517LF Romsey – Hampshire
United Kingdom
T + 44 (0) 1794 521111
info@wessex-resins.com - www.wessexresins.co.uk

1.4. Emergency telephone number

Emergency number : + 44 (0) 207 858 1228

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Edinburgh Centre) Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP], as amended for UK law

Acute toxicity (oral), Category 4 H302
Acute toxicity (inhalation:vapour) Category 4 H332

Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Corrosive to eyes and skin. Classified as a skin sensitizer. This product contains hazardous components for the environment.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP], as amended for UK law

Hazard pictograms (CLP) :



GHS05 GHS07 GHS09

Signal word (CLP) : Danger

Contains : m-phenylenebis(methylamine); Trimethylhexane-1,6-diamine; Phenol, styrenated; 2,4,6-tris(dimethylaminomethyl)phenol; 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Hazard statements (CLP) : H302+H332 - Harmful if swallowed or if inhaled.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P280 - Wear eye protection, face protection, protective gloves.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture contains substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component	
Phenol, styrenated(61788-44-1)	The substance is included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Labelling according to Regulation (EC) No 1272/2008 [CLP], as amended for UK law
m-phenylenebis(methylamine) substance with national workplace exposure limit(s) (AT, BE, DK, FI, FR, IE, PT, IS, NO, MK, CH)	CAS-No.: 1477-55-0 EC-No.: 216-032-5	≥ 30 – < 60	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Phenol, styrenated substance identified as having endocrine disrupting properties	CAS-No.: 61788-44-1 EC-No.: 262-975-0	≥ 10 – < 30	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411
Trimethylhexane-1,6-diamine	CAS-No.: 25513-64-8 EC-No.: 247-063-2	≥ 1 – < 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9	≥ 1 – < 5	Acute Tox. 4 (Oral), H302 (ATE=1030 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317
2,4,6-tris(dimethylaminomethyl)phenol	CAS-No.: 90-72-2 EC-No.: 202-013-9 EC Index-No.: 603-069-00-0	≥ 1 – < 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Irrit. 2, H315

Specific concentration limits:

Name	Product identifier	Specific concentration limits
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9	(0.001 ≤ C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing difficulties persist : Give oxygen or artificial respiration if necessary.

First-aid measures after skin contact : Wash immediately with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. Sensitisation : contact can cause allergic reactions in humans. Seek medical attention if ill effect develops.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth out with water. Do not induce vomiting. Give nothing or a little water to drink. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact : May cause sensitisation by skin contact. Causes severe burns. In case of repeated or prolonged exposure : irritation (itching, redness, blistering).
Symptoms/effects after eye contact : Causes serious eye damage. Exposed may experience eye tearing, redness and discomfort.
Symptoms/effects after ingestion : May cause discomfort. May cause stomach cramps and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. May cause sensitisation of susceptible persons by skin contact.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : If there is a fire close by, use suitable extinguishing agents. Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable. Heating will cause a rise in pressure with a risk of bursting. In the presence of water, forms corrosive solutions.
Explosion hazard : No data available on direct explosion hazard. No data available on indirect explosion hazard.
Hazardous decomposition products in case of fire : Toxic and corrosive vapours may be released.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area. Eliminate all ignition sources if safe to do so.
Firefighting instructions : Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Collect spillage. Dispose of contaminated materials in accordance with current regulations.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Keep away from combustible material.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Keep unnecessary and unprotected personnel away from the spillage. Turn leaking containers leak-side up to prevent the escape of liquid. For a large spillage, contain the spillage by bunding. Collect the residue by means of a non-combustible absorbent material. Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of contaminated materials in accordance with current regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Keep container tightly closed and away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage area : Store in a well-ventilated place.
Special rules on packaging : Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

m-phenylenebis(methylamine) (1477-55-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.2 mg/m³
Long-term - local effects, inhalation	0.2 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.094 mg/l
PNEC aqua (marine water)	0.0094 mg/l
PNEC aqua (intermittent, freshwater)	0.152 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12.4 mg/kg dwt
PNEC sediment (marine water)	1.24 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.44 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

Trimethylhexane-1,6-diamine (25513-64-8)	
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.05 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.102 mg/l
PNEC aqua (marine water)	0.0102 mg/l
PNEC aqua (intermittent, freshwater)	0.315 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.622 mg/kg dwt
PNEC sediment (marine water)	0.062 mg/kg dwt
PNEC (Soil)	
PNEC soil	10 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	72 mg/l

Phenol, styrenated (61788-44-1)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	2.1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	7.4 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.75 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.31 mg/m³
Long-term - systemic effects, dermal	0.75 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	4 µg/l
PNEC aqua (marine water)	0.4 µg/l
PNEC aqua (intermittent, freshwater)	46 µg/l
PNEC aqua (intermittent, marine water)	4.6 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.248 mg/kg dwt
PNEC sediment (marine water)	24.8 µg/kg dw
PNEC (Soil)	
PNEC soil	47.3 µg/kg dw
PNEC (STP)	
PNEC sewage treatment plant	36.2 mg/l

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	0.6 mg/kg bodyweight/day
Acute - systemic effects, inhalation	2.1 mg/m³
Long-term - systemic effects, dermal	0.15 mg/kg bodyweight/day

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Long-term - systemic effects, inhalation	0.53 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	0.075 mg/kg bodyweight/day
Acute - systemic effects, inhalation	0.13 mg/m³
Long-term - systemic effects,oral	0.075 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.13 mg/m³
Long-term - systemic effects, dermal	0.075 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.046 mg/l
PNEC aqua (marine water)	0.0046 mg/l
PNEC aqua (intermittent, freshwater)	0.46 mg/l
PNEC aqua (intermittent, marine water)	0.046 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.2621 mg/kg dwt
PNEC sediment (marine water)	0.026211 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0254 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0.2 mg/l

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.073 mg/m³
Long-term - local effects, inhalation	0.073 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0.3 mg/kg bodyweight/day
Long-term - systemic effects,oral	0.526 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.06 mg/l
PNEC aqua (marine water)	0.006 mg/l
PNEC aqua (intermittent, freshwater)	0.23 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	5784 mg/kg dwt
PNEC sediment (marine water)	0.578 mg/kg dwt
PNEC (Soil)	
PNEC soil	1121 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	3.18 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves, Reusable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	≥ 0.13		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:
Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Disposable half mask	Type A - High-boiling (>65 °C) organic compounds, Type P3	Protection for Liquid particles, Gas protection	EN 140, EN 14387
Reusable half mask	Type A - High-boiling (>65 °C) organic compounds, Type P3	Protection for Liquid particles, Gas protection	EN 140, EN 14387
Full face mask	Type A - High-boiling (>65 °C) organic compounds, Type P3	Protection for Liquid particles, Gas protection	EN 136, EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	colourless to pale yellow.
Appearance	:	Clear liquid.
Odour	:	Amine-like.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Non flammable.
Explosive properties	:	Not determined.
Oxidising properties	:	Does not meet the criteria for classification as oxidising.
Explosive limits	:	Not applicable
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	Not available
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	Not available
Viscosity, dynamic	:	25 @ 22°C
Solubility	:	In water, material soluble.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	1.03 @ 22°C
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

PRO-SET INF-210 HARDENER	
ATE CLP (oral)	732.278 mg/kg bodyweight
ATE CLP (vapours)	19.435 mg/l/4h

m-phenylenebis(methylamine) (1477-55-0)	
LD50 oral rat	930 mg/kg Source: ECHA
LD50 dermal rat	> 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 3100 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	1.12 mg/l Source: ECHA

Trimethylhexane-1,6-diamine (25513-64-8)	
LD50 oral rat	910 mg/kg bodyweight Animal: rat, Animal sex: male

Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 7940 mg/kg Source: KOSHAMSDS
LC50 Inhalation - Rat	> 4.92 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	1200 mg/kg
LD50 dermal rat	1280 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
LD50 oral rat	1030 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:

Skin corrosion/irritation : Causes severe skin burns.

Phenol, styrenated (61788-44-1)	
pH	6.85 Temp.: 30 °C Concentration: 1 vol%

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
pH	11

Serious eye damage/irritation : Causes serious eye damage.

Phenol, styrenated (61788-44-1)	
pH	6.85 Temp.: 30 °C Concentration: 1 vol%

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
pH	11

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Trimethylhexane-1,6-diamine (25513-64-8)	
LOAEL (oral, rat, 90 days)	60 mg/kg bodyweight Animal: rat
NOAEL (oral, rat, 90 days)	10 mg/kg bodyweight Animal: rat

Phenol, styrenated (61788-44-1)	
LOAEL (oral, rat, 90 days)	337 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
NOAEL (oral, rat, 90 days)	15 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
LOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
Viscosity, kinematic	19 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Component	
Phenol, styrenated(61788-44-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Toxic to aquatic life with long lasting effects.

Not rapidly degradable

m-phenylenebis(methylamine) (1477-55-0)	
LC50 - Fish [1]	87.6 mg/l
EC50 - Crustacea [1]	15.2 mg/l
EC50 72h - Algae [1]	20.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	33.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	33.3 mg/l Source: EHCA
LOEC (chronic)	15 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	4.7 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Trimethylhexane-1,6-diamine (25513-64-8)	
LC50 - Fish [1]	46.123 mg/l Source: EPISUITE
EC50 72h - Algae [1]	43.5 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1.644 mg/l Source: EPISUITE
LOEC (chronic)	1.02 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	1.02 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 10.9 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '30 d'

Phenol, styrenated (61788-44-1)	
LC50 - Fish [1]	1.77 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	4.6 mg/l
EC50 72h - Algae [1]	1.35 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	0.115 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 - Fish [1]	447.821 mg/l
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	46.7 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	25.5 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	34.812 mg/l Source: ECOSAR

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
LC50 - Fish [1]	110 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	23 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	37 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 50 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

m-phenylenebis(methylamine) (1477-55-0)	
Partition coefficient n-octanol/water (Log Pow)	0.18

Trimethylhexane-1,6-diamine (25513-64-8)	
Partition coefficient n-octanol/water (Log Pow)	1.11 Source: Lookchem

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	0.77

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
Partition coefficient n-octanol/water (Log Pow)	1.9

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

Component	
Phenol, styrenated(61788-44-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

HP Code : HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
HP8 - "Corrosive:" waste which on application can cause skin corrosion.
HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 2735
UN-No. (IMDG) : UN 2735
UN-No. (IATA) : UN 2735
UN-No. (ADN) : UN 2735
UN-No. (RID) : UN 2735

14.2. UN proper shipping name

Proper Shipping Name (ADR)	:	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated)
Proper Shipping Name (IMDG)	:	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated)
Proper Shipping Name (IATA)	:	Amines, liquid, corrosive, n.o.s. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated)
Proper Shipping Name (ADN)	:	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated)
Proper Shipping Name (RID)	:	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated)
Transport document description (ADR)	:	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated), 8, II, (E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	:	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated), 8, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	:	UN 2735 Amines, liquid, corrosive, n.o.s. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated), 8, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	:	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated), 8, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	:	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : m-phenylenebis(methylamine) ; Phenol, styrenated), 8, II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 8

Danger labels (ADR) : 8

:



IMDG

Transport hazard class(es) (IMDG) : 8

Danger labels (IMDG) : 8

:



IATA

Transport hazard class(es) (IATA) : 8

Danger labels (IATA) : 8

:



ADN

Transport hazard class(es) (ADN) : 8

Danger labels (ADN) : 8

:



RID

Transport hazard class(es) (RID) : 8

Danger labels (RID) : 8

:



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : C7

Special provisions (ADR) : 274

Limited quantities (ADR) : 1l

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02

Mixed packing provisions (ADR) : MP15

Portable tank and bulk container instructions (ADR) : T11

Portable tank and bulk container special provisions (ADR) : TP1, TP27

Tank code (ADR) : L4BN

Vehicle for tank carriage : AT

Transport category (ADR) : 2

Hazard identification number (Kemler No.) : 80

Orange plates :



Tunnel restriction code (ADR) : E

EAC code : 2X

Transport by sea

Special provisions (IMDG) : 274

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T11

Tank special provisions (IMDG) : TP1, TP27

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-B

Stowage category (IMDG) : A

Segregation (IMDG) : SGG18, SG35

Properties and observations (IMDG) : Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y840
PCA limited quantity max net quantity (IATA)	:	0.5L
PCA packing instructions (IATA)	:	851
PCA max net quantity (IATA)	:	1L
CAO packing instructions (IATA)	:	855
CAO max net quantity (IATA)	:	30L
Special provisions (IATA)	:	A3, A803
ERG code (IATA)	:	8L

Inland waterway transport

Classification code (ADN)	:	C7
Special provisions (ADN)	:	274
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E2
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EP
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	C7
Special provisions (RID)	:	274
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001, IBC02
Mixed packing provisions (RID)	:	MP15
Portable tank and bulk container instructions (RID)	:	T11
Portable tank and bulk container special provisions (RID)	:	TP1, TP27
Tank codes for RID tanks (RID)	:	L4BN
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE6
Hazard identification number (RID)	:	80

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

Abbreviations and acronyms:	
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety_Data_Sheet_SDS_EU_UK